

Programming A Standard Back-Lit Remote To Santel Set-Top-Boxes

Amino A140, A540, A130

Note Santel remotes generally come pre-programmed for all oval-shaped Amino boxes.

- 1) Press & Release “STB” button.
- 2) Press & Hold “Setup” button until the “STB” button blinks 3 times (may take 3-5 seconds).
- 3) Press #'s in sequence: **1-8-9-8**.
- 4) Verify Channel +/-, Guide, Menu buttons are working.



Innovative Systems IS-5112w

- 1) Press & Release “STB” button.
- 2) Press & Hold “Setup” button until the “STB” button blinks 3 times (may take 3-5 seconds).
- 3) Press #'s in sequence: **1-3-7-6**.
- 4) Verify Channel +/-, Guide, Menu buttons are working.



Note “S.T.B.” sticker may or may not be present or in the spot shown!*



Amino Kamai 7X/7B

- 1) Press & Release “STB” button.
- 2) Press & Hold the “Setup” button and the # **7** button at the same time until the STB button blinks twice (may take 3-5 seconds).
- 3) Verify Channel +/-, Guide, Menu buttons are working.

NOTE Some remotes may have issues programming correctly to this model. Please call our office if issues arise.





SANTEL REMOTE CONTROL PROGRAMMING

1. Turn on the TV.
2. On the Santel remote control, press & release the “TV” button once; it will blink once.
3. Press and hold “SETUP” until the “TV” button blinks twice (may take a few seconds)
4. Press in sequence: “9” “9” “1”. The TV button will blink twice.
5. Press and release the “CH+” key slowly & continuously. Stop when the TV turns off.
6. Press and release “SETUP” button.

DONE! *TEST POWER AND VOLUME!*

LOCKING REMOTE IN FOR MASTER POWER

(This shuts the power off to the Set-Top-Box & TV at the same time – can only be done after the remote has initially been programmed via the steps above.)

THIS STEP IS NOT CRUCIAL AND CAN BE SKIPPED IF DESIRED.

1. Press & release “STB”
2. Press and hold “SETUP” until the “STB” button flashes twice (may take a few seconds)
3. Press in sequence: “9” “9” “5”
4. Press & release the “POWER” button.
5. Press & release the “TV” button.
6. Press & hold “SETUP” until “TV” flashes twice.

DONE!

****Make sure you go back to “STB” mode on remote upon finishing for STB functions****

